

AD-A257 019

IN PAGE

Form Approved  
OMB No. 0704-0188

2

Public Rep  
Gathering  
Distribution  
Availability

Your per response including the time for reviewing instructions, searching existing data sources, collection of information, send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Avenue, Washington, DC 20540, and to the Office of Management and Budget, Paperwork Reduction Project (3704-0188), Washington, DC 20503.

1. AGEI

8/31/92

3. REPORT TYPE AND DATES COVERED

final report, 6/89-6/92

4. TITLE AND SUBTITLE

Dynamics of analog electronic neural networks

5. FUNDING NUMBERS

DAAL03-89-G-0076

6. AUTHOR(S)

Frederick R. Waugh

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Harvard University  
Cambridge, MA 02138DTIC  
ELECTE  
OCT 21 19928. PERFORMING ORGANIZATION  
REPORT NUMBER

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

U. S. Army Research Office  
P. O. Box 12211  
Research Triangle Park, NC 27709-221110. SPONSORING/MONITORING  
AGENCY REPORT NUMBER

ARO 27007.8-EL-F

11. SUPPLEMENTARY NOTES

The view, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

We review recent results on dynamics and stability of analog neural networks and discuss their application to associative memory and visual processing. Stability criteria for these networks guarantee convergence to fixed-point attractors under continuous-time and discrete-time, parallel updating. For associative memory, phase diagrams describing different attractor types are discussed, and it is shown that reducing analog transfer function steepness improves network performance. For visual processing, a two-dimensional, translation-invariant network is described. The network detects image features using a novel architecture that greatly reduces network wiring.

92 10 20 078

92-27536



11P8

14. SUBJECT TERMS

neural networks, associative memory, feature detection, image processing, analog computation

15. NUMBER OF PAGES

10

16. PRICE CODE

17. SECURITY CLASSIFICATION  
OF REPORT

UNCLASSIFIED

18. SECURITY CLASSIFICATION  
OF THIS PAGE

UNCLASSIFIED

19. SECURITY CLASSIFICATION  
OF ABSTRACT

UNCLASSIFIED

20. LIMITATION OF ABSTRACT

UL

# DYNAMICS OF ANALOG ELECTRONIC NEURAL NETWORKS

Final Report  
Frederick R. Waugh  
August 31, 1992

U. S. Army Research Office  
Grant Number DAAL03-89-G-0076  
Harvard University

Approved For	
THIS REPORT	<input checked="checked" type="checkbox"/>
FOR RELEASE	<input type="checkbox"/>
TO THE PUBLIC	<input type="checkbox"/>
Distribution Codes	
1.1	1.2
A-1	

Approved for public release;  
distribution unlimited.

The view, opinions, and/or findings contained in this report are those of the author and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

Table of Contents	page
Introduction . . . . .	3
Architecture of analog neural networks . . . . .	4
Stability results . . . . .	5
Analog associative memories . . . . .	6
Analog neural networks for visual processing . . . . .	7
Publications . . . . .	9
Participating scientific personnel . . . . .	10

## Figures

Fig. 1: standard and competitive analog networks . . . . .	4
Fig. 2: associative memory results . . . . .	7
Fig. 3: architecture of feature detector . . . . .	8
Fig. 4: performance of feature detector . . . . .	9

## Introduction

Drawing on statistical techniques for studying disordered systems like spin glasses, physicists have made remarkable contributions to the field of neural networks in the last decade. Nevertheless, hardware implementations of theoretical models based on spin glass ideas remain few. An important reason is that the stochastic, serial updating rules of these models place costly demands on circuit size and speed. The scarcity of implementations is particularly striking because neural networks must move off general-purpose computers and onto specialized hardware to achieve useful, real-time applicability.

Rather than trying to force theoretical models onto hardware, an alternate approach is to ask what features are readily implementable in hardware and to design neural networks accordingly. The research carried out under this grant has explored the dynamics of networks of *analog* neurons—characterized by a nonlinear input-output transfer function with finite slope or gain—updated *deterministically*, either in continuous time or in discrete

time with parallel updating. This report summarizes the most important results on the stability of these networks and on their application to associative memory and visual processing.

### Architecture of analog neural networks

Two network architectures, *standard* and *competitive* analog networks, have been studied in detail. The networks are depicted schematically in Fig. 1.




Fig. 1. Architecture of (a) standard and (b) competitive analog networks. Circles denote neurons, filled squares denote interconnections, ellipses in (b) denote competitive interaction. (c) Analog neuron input-output transfer function.

Standard analog networks are described by either the continuous-time equations

$$\frac{dx_i(t)}{dt} = -x_i(t) + F\left(\sum_{j=1}^N J_{ij}x_j(t)\right), \quad i = 1, \dots, N, \quad (1)$$

or by the discrete-time, parallel-update equations

$$x_i(t+1) = F \left( \sum_{j=1}^N J_{ij} x_j(t) \right), \quad i = 1, \dots, N, \quad (2)$$

where  $x_i(t)$  is the output of neuron  $i$  at time  $t$ ,  $F(z)$  is a nonlinear input-output transfer function, and  $J_{ij}$  is a symmetric interconnection matrix. These networks are useful for applications involving *binary* data—for example, black and white image pixels.

In competitive analog networks, neurons compete with each other in localized clusters containing  $Q$  neurons each. The networks are described by either the continuous-time equations

$$\frac{dx_{ia}(t)}{dt} = -x_{ia}(t) + F \left( \sum_{j=1}^N \sum_{b=1}^Q J_{ij}^{ab} x_{jb}(t) + B_i(t) \right), \quad (3)$$

or by the discrete-time, parallel-update equations

$$x_{ia}(t+1) = F \left( \sum_{j=1}^N \sum_{b=1}^Q J_{ij}^{ab} x_{jb}(t) + B_i(t) \right), \quad (4)$$

where  $x_{ia}(t)$  is the output of neuron  $a$  in cluster  $i$  at time  $t$ ,  $F(z)$  is a nonlinear input-output transfer function, and  $J_{ij}^{ab}$  is a symmetric interconnection matrix. The quantity  $B_i(t)$  enforces competition in cluster  $i$  by making the outputs of all neurons in the cluster sum to a constant at all times. The winner-take-all function, in which only one neuron having the largest input fires in each cluster, is an example of competitive behavior implementable with this mechanism. These networks are useful for applications involving *multiclass* data—for example, image pixels of several different colors.

## Stability results

Using a Liapunov function approach, we have studied the stability of standard and competitive analog networks. Stability is important in designing networks that compute by

relaxing to fixed-point attractors, for which oscillation is undesirable. Our most important result is that analog neurons can be updated in parallel without oscillation, a crucial advantage over two-state neurons for real-time processing.

With continuous-time updating, both standard and competitive analog networks always converge to fixed-point attractors. With discrete-time parallel updating, both network types converge only to fixed points when the slopes of the transfer functions are sufficiently small but can oscillate for large slopes. The condition guaranteeing convergence is  $1/\beta > -\lambda_{\min}$ . For standard networks,  $\beta$  is the steepest slope of the transfer function, and  $\lambda_{\min}$  is the minimum eigenvalue of  $J_{ij}$ . For competitive networks,  $\beta$  is a measure of the steepness of all  $Q$  transfer functions in a cluster, and  $\lambda_{\min}$  is the minimum eigenvalue of  $J_{ij}^{ab}$ .

### Analog associative memories

We have studied the attractors of standard and competitive analog networks configured as associative memories that store patterns of neuron activity. Our most important results are (i) analytical phase diagrams describing the different attractor types as a function of the transfer function slope  $\beta$  and the ratio  $\alpha$  of patterns to neurons, and (ii) analytical results showing that the number of spurious attractors decreases as the transfer function slope is reduced. The phase diagrams provide quantitative guidelines for designing and operating associative memories by indicating regions of parameter space where memory recall is possible as well as regions where spurious fixed points or oscillatory attractors exist. The results on spurious attractors have implications for improving performance in analog computers that solve complex optimization problems.

A typical phase diagram is shown in Fig. 2(a) for standard analog associative memories with discrete-time, parallel updating. The diagram has four regions called recall, oscillatory, spin glass, and paramagnetic. In the recall region, the networks operate reliably as associative memories, with fixed points corresponding to stored patterns; in the oscillation region, the stability criterion discussed above is violated; in the spin glass region, no recall fixed points exist, but there are numerous spurious fixed points; and in the paramagnetic region, there is a single attractor with all neuron outputs zero.




Fig. 2. (a) Phase diagram showing recall, oscillatory, spin glass, and paramagnetic regions. (b) Exponent  $g(\alpha, \beta)$ . Number of spurious fixed points varies as  $e^{Ng}$ .

Results on spurious attractors in standard analog associative memories are shown in Fig. 2(b). We find that the number of spurious attractors varies with network size  $N$  as  $e^{Ng}$ . The exponent  $g(\alpha, \beta)$  depends on the transfer function slope  $\beta$  and on the ratio  $\alpha$  of patterns to neurons. As shown in the figure, the exponent decreases as the slope decreases. This implies that the number of spurious attractors is reduced and the network performance improved as the slope is lowered.

### Analog neural networks for visual processing

We have also investigated two-dimensional analog networks for translation-invariant feature detection in visual scenes. Our main result is that competitive analog networks are extremely well-suited for visual feature detection, performing difficult tasks with simple, sparse wiring configurations.






Fig. 3. Architecture of a two-dimensional competitive feature detector.

Figure 3 depicts the architecture of a competitive feature detector. Each neuron in a competitive cluster represents a fragment of a feature to be detected. Neurons receive inputs both from a localized region of a pixel array and from neurons in neighboring clusters. The interconnections between clusters are designed to reconstruct complete features from their constituent fragments. These networks can successfully detect features in noisy images with translation invariance on the length scale of the feature fragments.

Figure 4 shows the initial and final pixel array of a network that recognizes two features, a star and a triangle. Each  $7 \times 7$  pixel block feeds into a single cluster of 9 competing neurons; the entire network needs only  $6 \times 6 = 36$  clusters,  $36 \times 9 = 324$  neurons, and  $36 \times 20 = 720$  interconnections to process an array of  $36 \times 49 = 1764$  pixels. The savings in wiring—the interconnections scale *linearly* with pixels—comes about because interconnections transmit information about entire features, rather than individual pixels.




Fig. 4. (a) Initial and (b) final pixel array of a competitive feature detector.

## Publications

F. R. Waugh, C. M. Marcus, and R. M. Westervelt, "Nonlinear dynamics of analog associative memory neural networks," in *Proceedings of the International Joint Conference on Neural Networks* (Hillsdale, NJ: Lawrence Erlbaum Associates, 1990).

C. M. Marcus, F. R. Waugh, and R. M. Westervelt, "Associative memory in an analog iterated-map neural network," *Phys. Rev. A* **41**, 3355 (1990).

F. R. Waugh, C. M. Marcus, and R. M. Westervelt, "Fixed-point attractors in analog neural computation," *Phys. Rev. Lett.* **64**, 1986 (1990).

C. M. Marcus, F. R. Waugh, and R. M. Westervelt, "Connection topology and dynamics in lateral inhibition networks," in *Advances in Neural Information Processing Systems*, Vol. 3 (San Mateo, CA: Morgan Kaufman Publishers, 1991).

F. R. Waugh, C. M. Marcus, and R. M. Westervelt, "Reducing neuron gain to eliminate fixed-point attractors in an analog associative memory," *Phys. Rev. A* **43**, 3131 (1991).

C. M. Marcus, F. R. Waugh, and R. M. Westervelt, "Nonlinear dynamics and stability of analog neural networks," *Physica D* **51**, 234 (1991).

F. R. Waugh, C. M. Marcus, and R. M. Westervelt, "Nonlinear dynamics of analog associative memories," in *Neural Memories: Theory and Implementation*, ed. M. Hassoun (Oxford University Press, in press).

F. R. Waugh and R. M. Westervelt, "Dynamics of analog neural networks with local competition," to appear in *Phys. Rev. A*.

F. R. Waugh and R. M. Westervelt, "Associative memory in analog neural networks with local competition," to appear in *Phys. Rev. A*.

#### **Participating scientific personnel**

Frederick R. Waugh